

TK-2212LK / 3212LK VHF/UHF Conventional Portable Radios



All 212L series portables include:

- Li-ion Battery (KNB-45L)
- Fast Charger (KSC-35K)
- Antenna [KRA-26M (VHF)/27M (UHF)]
- Belt Clip (KBH-10)
- 2-PIN Connector Cap
- Instruction Manual

GENERAL FEATURES

- 5 W (136-174 MHz) Model
- 4 W (450-490 MHz) Model
- Conventional Zones
- 128 Channels / 128 Zones
- Single Priority Scan
- Single & Multi-Zone Scan
- 8 Character Alphanumeric Aliases
- Backlit LCD
- Function / Status LCD Icons
- Transmit / Busy / Call Alert / Warn LED
- 4 Front PF Keys
- 2 Side PF Keys
- 500 mW Audio Power
- Enhanced Kenwood Audio
- Companded Audio
- VOX Ready
- Voice Inversion Scrambler Built-in
- QT / DQT
- Operator Selectable Tone
- DTMF Encode / Decode
- Special Alert Tone Pattern
- Call Key
- Time Out Timer

- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- Speaker Mic Options
- Windows® Programming & Tuning
- Field Programming & Tuning
- Wireless Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion

FleetSync®

- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging
- Caller ID Display
- Short Text Message

RADIO

TK-2212LK	136-174 MHz VHF 5W, 128 Ch.
TK-3212LK	450-490 MHz VHF 4W, 128 Ch.

BATTERIES AND CHARGERS

KNB-45L	2000 mAh, Li-ion battery - requires KSC-35K/E charger
KNB-29N	1500 mAh, NiMH battery - requires KSC-31K/E charger
KSC-35K	110 volt Fast rate single unit charger for KNB-45L Li-ion battery
KSC-31K	110 volt Fast rate single unit charger for KNB-29N