

TK-7360HV / 8360HU V2.0

VHF/UHF Conventional Mobile Radios



All 360 series mobiles include:

- Standard Microphone (KMC-35)
- Mounting Bracket
- DC Cable (KCT-23M)
- 15A Fuse
- Instruction Manual
- Standard Warranty: 2 Years*

* All Accessories / options: 1 Year

GENERAL FEATURES

- 50 W (136-174 MHz) Model
- 45 W (450-520 MHz) Model
- Conventional & LTR® Zones
- 10-Character Alphanumeric Aliases
- Backlit LCD & Keys
- Function/Status LCD Icons
- Blue Function / Status LED
- Transmit /Busy / Call Alert LED
- 10 Programmable Function Keys
- Emergency / AUX Key
- Front Panel Speaker
- Companded Audio
- Voice Inversion Scrambler Built-in
- 16 Scrambler Codes (per CH)
- Encryption / Board Control
- Emergency Call Features
- Lone Worker Alert
- DTMF Encode / Decode
- Special Alert Tone Patterns
- Busy Channel Lockout
- Time Out Timer
- Timed Power Off
- DB15 Accessory Interface
- 8 Programmable I/O Ports
- Ignition Sense
- Public Address / Horn Alert Output
- MIL-Spec Standard Mic
- MIL-Spec 12-Key DTMF Mic Option
- Windows® Programming & Tuning
- Easy Option Ports (26-pin)
- Cloning
- Voice Guide & Storage (Option)
- MIL-STD-810 C/D/E/F/G
- IP54 Water & Dust Intrusion

CONVENTIONAL ZONES

- 128 Channels / 128 Zones
- QT / DQT
- Two-Tone Decode
- Single & Two-Tone Encode
- Operator Selectable Tone
- Single Priority Scan
- Single / Multi-Zone Scan

TRUNKED ZONES

- 128 GID / 128 Zones
- Kenwood LTR® Feature

FleetSync® /II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Paging Call
- Status Messaging
- Emergency Status
- Caller ID Display
- Input / Output Status Messages
- FleetSync® GPS Ready
- Send GPS PF Key
- PTT ID & Emergency GPS Reporting
- GPS Auto Reporting

MDC-1200

- PTT ID Digital ANI
- Caller ID Display
- Emergency Status
- Radio Check
- Radio Inhibit

MODEL

TK-7360HVK	136-174 MHz 50W, 128 CH / 128 Zone Conventional
TK-8360HUK	450-520 MHz 45W, 128 CH / 128 Zone Conventional

MOBILE INSTALLATION ACCESSORIES

KCT-60M	DB15-to-15pin Molex Adapter Cable
KCT-18	Ignition sense cable (requires KCT-60M Acc. Cable Option)
KCT-36	Extension Cable for KCT-34/35/39/40M/60M; 117.6 inches (9.8 ft)
KLF-2	Line Filter (suppresses alternator whine, 25dB, 25A max).
KMB-10	Key lock adapter

CONTROL STATION INSTALLATION ACCESSORIES

KMC-9C	Control Station Desktop Microphone (8-pin mod. plug)
KMB-24	Control Station Mounting Case for KPS-15 Power Supplies (mobile mounting hardware included)
KPS-15	DC Switching Power Supply (117/230 VAC; 23A max. continuous, 25A peak)